

28-NOV-2003 17:49 VDN:KERSCHER PRUENTE

08213499662

AN:0010130017186011099 S:9

Se 09P02 US
28.11.03

7

I CLAIM:

1. Handling device placed on a wall of a vehicle in a removable manner, attached removably by means of a fastener.
2. Handling device in accordance with claim 1 wherein the handling device is placed above a recess in a wall.
3. Handling device in accordance with claim 1 wherein the device is held in the wall by means of a snap-together joint or by means of magnetic elements in the wall.
4. Handling device in accordance with claim 3 wherein the device comprises tabs or notches on a side wall or on a side facing the depression, which interact with notches or recesses at the depression.
5. Handling device in accordance with claim 2 wherein the recess has a depression in the center console of a motorized vehicle.
6. Handling device in accordance with claim 1 wherein the device comprises at least one opening for handling.
7. Handling device in accordance with claim 6 wherein is provided an opening for handling with a diameter larger than that of a beverage bottle or a beverage can.
8. Handling device in accordance with claim 7 wherein the opening for handling features a lip around parts of or the entire circumference, made of an elastic material, in particular of rubber.
9. Handling device in accordance with claim 1 wherein the device comprises a recess of its lateral, external contour, by means of which the handling device can be grasped.
10. Handling device in accordance with claim 1 wherein a tool (in particular, an ice scraper, a screwdriver, a bottle opener, or similar object) is placed on the handling device.
11. Handling device in accordance with claim 10 wherein at least one lip protruding from its lateral, external contour, is provided which is in particular made of a hard or a soft plastic, in particular with a pointed, external edge.

28-NOV-2003 17:50 VDN:KERSCHER PRUENTE

08213499662

AN:0010130017186011099 S:10

Se 09P02 US
28.11.03

8

12. Handling device in accordance with claim 11 wherein corrugation on the handling device is provided, in particular on the underside, in particular near a narrow side of the handling device.
13. Handling device in accordance with claim 1 wherein an opening is provided, in particular for accepting at least one coin or a bottle opener.
14. Handling device in accordance with claim 1 wherein a light fixture is provided, in particular a light-emitting diode.
15. Handling device in accordance with claim 1 wherein the device consists of two flat elements which are joined unseverably.
16. Handling device in accordance with claim 15 wherein at least one lip or a plate is provided between the elements, which protrudes laterally outward.
17. Handling device in accordance with claim 15 wherein a rechargeable battery or a battery and a light fixture are placed between the elements.